



ISSUE 16 JANUARY 2009

<h1>Lamborghini</h1>			With Parallel Linkage								Alternative hydraulic solutions				
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85 DL	Subframe	Standard Hydraulic Kit	CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel													
Crono Target 55 and Target 70	26	280/85 R24	X									14,310,565	10,317,794		
GRAND PRIX 674-70	3,4,8,11	420/85 R24				X	X					14,322,175	10,317,735	10,367,735	
GRAND PRIX 774-80	3,4,8,10	420/85 R24				X	X					14,321,835	10,317,735	10,367,735	
GRAND PRIX 874-90	3,4,8,9	420/85 R24				X	X					14,321,835	10,317,735	10,367,735	
GRAND PRIX Target 75	3,4,8	420/85 R24				X	X					14,322,175	10,317,735	10,367,735	
GRAND PRIX Target 95	3,4,8	420/85 R24				X	X					14,321,835	10,317,735	10,367,735	
Premium 850, 950 and 1050	3,13,14	420/85 R24					X	X				14,322,185	10,317,743	10,367,743	
Premium 1060	3,5,13,14	420/85 R24					X	X				14,321,985	10,317,743	10,367,743	
Premium 1100	3,13	480/70 R28							X	X		14,321,575	10,317,716	10,367,716	
Premium 1300	3,13	540/65 R30							X	X		14,321,575	10,317,716	10,367,716	
R2.56 and R2.56E Target		360/70 R20	X		X							14,310,515	10,317,752	10,367,752	
R2.65, R2.66, R2.66E Target and Sprint 664-65	19	360/70 R20	X		X							14,310,515	10,317,752	10,367,752	
R2.76, R2.76E Target, Sprint 674-70 and Sprint 674-75		320/70 R24	X		X							14,310,495	10,317,752	10,367,752	
R2.85, R2.86, R2.86E Target and Sprint 684-85	16	320/70 R24	X		X							14,310,495	10,317,752	10,367,752	
R3.75, R3.85 and R3.95	3,4,8,12	420/70 R24				X	X					14,322,045	10,317,740	10,367,740	
R3.75T, R3.75TB, R3.85T, R3.85TB, R3.95T and R3.95TB		320/70 R24				X	X					14,322,165	10,317,746		
R3.85 EVO and R3.100 EVO	8	420/85 R24				X	X					14,324,585	10,317,807	10,367,807	
R4.85, R4.95 and R4.110	3,13	420/85 R24					X	X				14,322,185	10,317,743	10,367,743	

3 Subframe set will fit with and without original front hitch
 4 Subframe not adapted for under slung (horizontal) exhaust pipe.
 5 Loader Q45 must be ordered with long bearing boxes.
 8 Loader Q35 must be ordered with long bearing boxes.
 9 From serial No: 22469.
 10 From serial No: 21296.
 11 From Serial No: 22797.
 12 Order hydraulic set: 10317742/10367742 for tractors with NO hydraulic trailer brake valve.

13 Does NOT fit tractors equipped with extended frontweight support.
 14 Does not fit tractors with LOW FRONT
 16 For tractors with vertical or cab mounted exhaust, please order 14310475.
 19 For tractors with vertical or cab mounted exhaust, please order 14310505.
 26 Adapted only for 2 point foldable ROPS.



ISSUE 16 JANUARY 2009

<h1>Lamborghini</h1>			With Parallel Linkage									Alternative hydraulic solutions			
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85 DL	Subframe	Standard Hydraulic Kit	CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel													
R4.105	3,5,13	420/85 R24					X	X			14,321,985	10,317,743	10,367,743		
R5.115		480/70 R28							X	X	14,321,575	10,317,716	10,367,716		
R5.130		540/65 R30							X	X	14,321,575	10,317,716	10,367,716		
R6.100, R6.110 4-cyl, R6.120 and R6.125	1,2,18,27,28					X	X				14,322,824	10,317,739	10,367,739		
R6.100 Hi-Profile, R6.110 Hi-Profile 4-cyl, R6.120 Hi-Profile and R6.125 Hi-Profile	1,18,25				X	X					14,322,824		10,367,763	10,377,232	
R6.110 6-cyl and R6.115	1,2,27,28						X	X			14,322,774	10,317,739	10,367,739		
R6.110 Hi-Profile 6-cyl and R6.115 Hi-Profile	1,25						X	X			14,322,774		10,367,763	10,377,232	
R6.130 and R6.150	2,6,17,23,24,29	540/65 R28					X	X			14,320,024	10,317,548	10,367,548		
R6.130 DCR Euro3, R6.140 and R6.160	2,17,24	540/65 R28					X	X			14,324,124	10,317,771	10,367,771		
R6.130 Hi-Profile	17	540/65 R28					X	X			14,320,024		10,367,771	10,377,284	
R6.130 Hi-Profile DCR Euro3, R6.140 Hi-Profile and R6.160 Hi-Profile	17	540/65 R28					X	X			14,324,124		10,367,771		
R6.130S and R6.150S	2,7,17,29							X	X		14,320,014	10,317,548	10,367,548		
R6.130S and R6.150S	2,6,17,29						X	X			14,320,024	10,317,548	10,367,548		
R6.140S and R6.165S	2,17,29							X	X		14,320,014	10,317,548	10,367,548		
R6.150 Hi-Profile	17,25	540/65 R28					X	X			14,320,024		10,367,771	10,377,284	
R6.150 VRT and R6.170 VRT	17	540/65 R28						X	X		14,324,084		10,367,563	10,377,146	
R6.150.7 and R6.165.7	2,17,23,24,29	540/65 R28						X	X		14,320,014	10,317,548	10,367,548		
R6.150.7 Hi-Profile and R6.165.7 Hi-Profile	17,25	540/65 R28						X	X		14,320,014		10,367,771	10,377,284	

- 1 Subframe adapted for tractors with Carraro front axle, with or without suspension.
- 2 Subframe adapted for tractors with or without front axle suspension.
- 3 Subframe set will fit with and without original front hitch
- 5 Loader Q45 must be ordered with long bearing boxes.
- 6 Adapted for engine type BF6M2012C
- 7 Adapted for engine type BF6M1013EC
- 13 Does NOT fit tractors equipped with extended frontweight support.
- 17 If the tractor have/should be equipped with Sauter front-hitch, contact Sauter for more information.
- 18 Use counter weight 1000 kg in combination with loader Q55.
- 23 If the tractor is manufactured after 2006-09-01 order 10317771/10367771

- 24 Tractors manufactured after 2006-09-01 without front axle suspension or piston pump a special plug is needed for L-S signal Order from SDF. Ref no:04454514.4
- 25 When fitting hose kit, 4 of the tractors quick couplers are moved to a higher position.
- 27 If the tractor has a 75 litre pump and a BOSCH valve then order hydraulic set 10317818/10367818
- 28 If tractor has a 75 litre pump and a BOSCH valve and NO front axle suspension a special plug is needed for L-S signal Order from SDF. Ref no:04454514.4
- 29 Tractors manufactured before 2006-09-01 tractor valve must be equipped with an end cover plate for LS signal Order from SDF. Ref no: Bosch 1525 503 538, S DFA 0441 3341



ISSUE 16 JANUARY 2009

<h1>Lamborghini</h1>			With Parallel Linkage									Alternative hydraulic solutions				
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85 DL	Subframe	Standard Hydraulic Kit	CDC Hydraulic Kit	De Luxe Hose Kit	Special Hose Kit
Tractor model	Rem.	Max front wheel														
R6.150.7 VRT and R6.165.7 VRT	17	540/65 R28							X	X		14,320,014		10,367,563	10,377,146	
R6.175	2,17,24	540/65 R28							X	X		14,324,084	10,317,771	10,367,771		
R6.175 Hi-Profile	17	540/65 R28							X	X		14,324,084		10,367,771		
R6.180.7 Hi-Profile	17,25	540/65 R34								X		14,322,874		10,367,771	10,377,284	
R6.185	2,24	540/65 R34								X		14,324,064	10,317,771	10,367,771		
R6.185 Hi-Profile		540/65 R34								X		14,324,064		10,367,771		

2 Subframe adapted for tractors with or without front axle suspension.
 17 If the tractor have/should be equipped with Sauter front-hitch, contact Sauter for more information.
 24 For tractors manufactured after 2006-09-01 and without front axle suspension or piston pump a special plug is needed for L-S signal. Order from SDF. Ref no:04454514.4
 25 When fitting hose kit, 4 of the tractors quick couplers are moved to a higher position.