



ISSUE 15 MARCH 2010

| <h1>Lamborghini</h1>                                  |                |                 | With Parallel Linkage |     |        |     |     |     |     |     |         | Alternative hydraulic solutions |                                  |                                |                  |
|---|----------------|-----------------|-----------------------|-----|--------|-----|-----|-----|-----|-----|---------|---------------------------------|----------------------------------|--------------------------------|------------------|
|   |                |                 | Q25 DS                | Q25 | Q35 DS | Q35 | Q45 | Q55 | Q65 | Q75 | Q85x DL | Subframe                        | ErgoDrive Standard Hydraulic Kit | ElectroDrive CDC Hydraulic Kit | De Luxe Hose Kit |
| Tractor model   | Rem.           | Max front wheel |                       |     |        |     |     |     |     |     |         |                                 |                                  |                                |                  |
| Crono 65, Crono 75, Rekord 65 and Rekord 75           | 28,29,30,31,32 | 280/85 R20      | X                     |     |        |     |     |     |     |     |         | 14,310,595                      | 10,317,838                       |                                |                  |
| Crono Target 55 and Target 70                         | 24             | 280/85 R24      | X                     |     |        |     |     |     |     |     |         | 14,310,565                      | 10,317,794                       |                                |                  |
| GRAND PRIX 674-70                                     | 3,4,8,11       | 420/85 R24      |                       |     |        | X   | X   |     |     |     |         | 14,322,175                      | 10,317,735                       | 10,367,735                     |                  |
| GRAND PRIX 774-80                                     | 3,4,8,10       | 420/85 R24      |                       |     |        | X   | X   |     |     |     |         | 14,321,835                      | 10,317,735                       | 10,367,735                     |                  |
| GRAND PRIX 874-90                                     | 3,4,8,9        | 420/85 R24      |                       |     |        | X   | X   |     |     |     |         | 14,321,835                      | 10,317,735                       | 10,367,735                     |                  |
| GRAND PRIX Target 75                                  | 3,4,8          | 420/85 R24      |                       |     |        | X   | X   |     |     |     |         | 14,322,175                      | 10,317,735                       | 10,367,735                     |                  |
| GRAND PRIX Target 95                                  | 3,4,8          | 420/85 R24      |                       |     |        | X   | X   |     |     |     |         | 14,321,835                      | 10,317,735                       | 10,367,735                     |                  |
| Premium 850, 950 and 1050                             | 3,13,14        | 420/85 R24      |                       |     |        |     | X   | X   |     |     |         | 14,322,185                      | 10,317,743                       | 10,367,743                     |                  |
| Premium 1060  | 3,5,13,14      | 420/85 R24      |                       |     |        |     | X   | X   |     |     |         | 14,321,985                      | 10,317,743                       | 10,367,743                     |                  |
| Premium 1100  | 3,13           | 480/70 R28      |                       |     |        |     |     | X   | X   |     |         | 14,321,575                      | 10,317,716                       | 10,367,716                     |                  |
| Premium 1300  | 3,13           | 540/65 R30      |                       |     |        |     |     | X   | X   |     |         | 14,321,575                      | 10,317,716                       | 10,367,716                     |                  |
| R2.56 and R2.56E Target                               |                | 360/70 R20      | X                     |     | X      |     |     |     |     |     |         | 14,310,515                      | 10,317,752                       | 10,367,752                     |                  |
| R2.60 and R2.80                                       |                | 320/85 R20      |                       | X   |        | X   |     |     |     |     |         | 14,325,095                      | 10,317,865                       | 10,367,865                     |                  |
| R2.65, R2.66, R2.66E Target and Sprint 664-65         | 19             | 360/70 R20      | X                     |     | X      |     |     |     |     |     |         | 14,310,515                      | 10,317,752                       | 10,367,752                     |                  |
| R2.76, R2.76E Target, Sprint 674-70 and Sprint 674-75 |                | 320/70 R24      | X                     |     | X      |     |     |     |     |     |         | 14,310,495                      | 10,317,752                       | 10,367,752                     |                  |
| R2.85, R2.86, R2.86E Target and Sprint 684-85         | 16             | 320/70 R24      | X                     |     | X      |     |     |     |     |     |         | 14,310,615                      | 10,317,752                       | 10,367,752                     |                  |
| R2.90   | 33             | 320/70 R24      |                       | X   |        | X   |     |     |     |     |         | 14,325,085                      | 10,317,865                       | 10,367,865                     |                  |

3 Subframe set will fit with and without original front hitch  
 4 Subframe not adapted for under slung (horizontal) exhaust pipe.  
 5 Loader Q45 must be ordered with long bearing boxes.  
 8 Loader Q35 must be ordered with long bearing boxes.  
 9 From serial No: 22469.  
 10 From serial No: 21296.  
 11 From Serial No: 22797.  
 13 Does NOT fit tractors equipped with extended frontweight support.  
 14 Does not fit tractors with LOW FRONT  
 16 For tractors with vertical or cab mounted exhaust, please order 14310615.

19 For tractors with vertical or cab mounted exhaust, please order 14310505.  
 24 Adapted only for 2 point foldable ROPS.  
 28 Designed for tractors with under slung exhaust pipe.  
 29 Will only fit 4wd tractors.  
 30 Because of the tractors design, a pressure reducing valve is included that lowers the loaders working pressure to 100 Bar.  
 31 The subframe set is adapted for tractors with 2 point foldable ROPS or Lochmann cab.  
 32 Observe that loader Q25 is not adapted for tractors with Lochmann cab.  
 33 Loader Q25 does not fit in combination with front linkage.



ISSUE 15 MARCH 2010

| <h1>Lamborghini</h1>  |                 |                 | With Parallel Linkage |     |        |     |     |     |     |     | Subframe | ErgoDrive<br>Standard<br>Hydraulic Kit | Alternative hydraulic solutions |                                      |                     |
|---|-----------------|-----------------|-----------------------|-----|--------|-----|-----|-----|-----|-----|----------|--|---------------------------------|--------------------------------------|---------------------|
|   |                 |                 | Q25 DS                | Q25 | Q35 DS | Q35 | Q45 | Q55 | Q65 | Q75 |          |  | Q85x DL                         | ElectroDrive<br>CDC<br>Hydraulic Kit | De Luxe<br>Hose Kit |
| Tractor model   | Rem.            | Max front wheel |                       |     |        |     |     |     |     |     |          |  |                                 |                                      |                     |
| R3.75 , R3.85 and R3.95   | 3,4,8,12        | 420/70 R24      |                       |     |        | X   | X   |     |     |     |          | 14,322,045                             | 10,317,740                      | 10,367,740                           |                     |
| R3.75T, R3.75TB, R3.85T, R3.85TB, R3.95T and R3.95TB                                |                 | 320/70 R24      |                       |     |        | X   | X   |     |     |     |          | 14,322,165                             | 10,317,746                      |                                      |                     |
| R3.85 EVO, R3.100 EVO and R3.110 EVO  | 8               | 420/85 R24      |                       |     |        | X   | X   |     |     |     |          | 14,324,585                             | 10,317,807                      | 10,367,807                           |                     |
| R4.85, R4.95 and R4.110   | 3,13            | 420/85 R24      |                       |     |        |     | X   | X   |     |     |          | 14,322,185                             | 10,317,743                      | 10,367,743                           |                     |
| R4.105  | 3,5,13          | 420/85 R24      |                       |     |        |     | X   | X   |     |     |          | 14,321,985                             | 10,317,743                      | 10,367,743                           |                     |
| R5.115  |                 | 480/70 R28      |                       |     |        |     |     |     | X   | X   |          | 14,321,575                             | 10,317,716                      | 10,367,716                           |                     |
| R5.130  |                 | 540/65 R30      |                       |     |        |     |     |     | X   | X   |          | 14,321,575                             | 10,317,716                      | 10,367,716                           |                     |
| R6.100, R6.110 4-cyl, R6.120 and R6.125   | 1,2,18,25,26    |                 |                       |     |        |     | X   | X   |     |     |          | 14,322,824                             | 10,317,739                      | 10,367,739                           |                     |
| R6.100 Hi-Profile, R6.110 Hi-Profile 4-cyl, R6.120 Hi-Profile and R6.125 Hi-Profile | 1,18,23         |                 |                       |     |        |     | X   | X   |     |     |          | 14,322,824                             |                                 | 10,367,763                           | 10,377,232          |
| R6.110 6-cyl and R6.115   | 1,2,25,26       |                 |                       |     |        |     |     | X   | X   |     |          | 14,322,774                             | 10,317,739                      | 10,367,739                           |                     |
| R6.110 Hi-Profile 6-cyl and R6.115 Hi-Profile                                       | 1,23            |                 |                       |     |        |     |     | X   | X   |     |          | 14,322,774                             |                                 | 10,367,763                           | 10,377,232          |
| R6.130 and R6.150   | 2,6,17,21,22,27 | 540/65 R28      |                       |     |        |     |     | X   | X   |     |          | 14,320,024                             | 10,317,548                      | 10,367,548                           |                     |
| R6.130 DCR Euro3, R6.140 and R6.160   | 2,17,22         | 540/65 R28      |                       |     |        |     |     | X   | X   |     |          | 14,324,124                             | 10,317,771                      | 10,367,771                           |                     |
| R6.130 Hi-Profile   | 17              | 540/65 R28      |                       |     |        |     |     | X   | X   |     |          | 14,320,024                             |                                 | 10,367,771                           | 10,377,284          |
| R6.130 Hi-Profile DCR Euro3, R6.140 Hi-Profile and R6.160 Hi-Profile                | 17,20           | 540/65 R28      |                       |     |        |     |     | X   | X   |     |          | 14,324,124                             |                                 | 10,367,771                           | 10,377,307          |
| R6.130S and R6.150S   | 2,7,17,27       |                 |                       |     |        |     |     |     | X   | X   |          | 14,320,014                             | 10,317,548                      | 10,367,548                           |                     |
| R6.130S and R6.150S   | 2,6,17,27       |                 |                       |     |        |     |     |     | X   | X   |          | 14,320,024                             | 10,317,548                      | 10,367,548                           |                     |

- 1 Subframe adapted for tractors with Carraro front axle, with or without suspension.
- 2 Subframe adapted for tractors with or without front axle suspension.
- 3 Subframe set will fit with and without original front hitch
- 4 Subframe not adapted for under slung (horizontal) exhaust pipe.
- 5 Loader Q45 must be ordered with long bearing boxes.
- 6 Adapted for engine type BF6M2012C
- 7 Adapted for engine type BF6M1013EC
- 8 Loader Q35 must be ordered with long bearing boxes.
- 12 Order hydraulic set: 10317742/10367742 for tractors with NO hydraulic trailer brake valve.
- 13 Does NOT fit tractors equipped with extended frontweight support.

- 17 If the tractor have/should be equipped with Sauter front-hitch, contact Sauter for more information.
- 18 Use counter weight 1000 kg in combination with loader Q55.
- 20 Hose kit Deluxe 10377307 does not fit tractors with air pressure equipment.
- 21 If the tractor is manufactured after 2006-09-01 order 10317771/10367771
- 22 Tractors manufactured after 2006-09-01 and without front axle suspension or piston pump a special plug is needed for L-S signal, order from SDF. Ref no:04454514.4
- 23 When fitting hose kit "Deluxe", 4 of the tractors quick couplers are moved to a higher position.
- 25 If the tractor has a 75 litre pump and a BOSCH valve then order hydraulic set 10317818/10367818
- 26 Tractors with 75 litre pump and a BOSCH valve and NO front axle suspension a special plug is needed for L-S signal, order from SDF. Ref no:04454514.4
- 27 Tractor manufactured before 2006-09-01, tractor valve must be equipped with an end cover plate for LS signal, order from SDF. Ref no: Bosch 1525 503 538, S DFA 0441 3341



ISSUE 15 MARCH 2010

| <h1>Lamborghini</h1>                        |               |                 | With Parallel Linkage |     |        |     |     |     |     |     | Subframe   | ErgoDrive<br>Standard<br>Hydraulic Kit | Alternative hydraulic solutions |                                      |                     |
|---|---------------|-----------------|-----------------------|-----|--------|-----|-----|-----|-----|-----|------------|--|---------------------------------|--------------------------------------|---------------------|
|   |               |                 | Q25 DS                | Q25 | Q35 DS | Q35 | Q45 | Q55 | Q65 | Q75 |            |  | Q85x DL                         | ElectroDrive<br>CDC<br>Hydraulic Kit | De Luxe<br>Hose Kit |
| Tractor model                               | Rem.          | Max front wheel |                       |     |        |     |     |     |     |     |            |  |                                 |                                      |                     |
| R6.140S and R6.165S                         | 2,17,27       |                 |                       |     |        |     |     | X   | X   |     | 14,320,014 | 10,317,548                             | 10,367,548                      |                                      |                     |
| R6.150 Hi-Profile                           | 15,17,23      | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,320,024 |  | 10,367,771                      | 10,377,284                           |                     |
| R6.150 VRT and R6.170 VRT                   | 17            | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,324,084 |  | 10,367,563                      | 10,377,146                           |                     |
| R6.150.7 and R6.165.7                       | 2,17,21,22,27 | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,320,014 | 10,317,548                             | 10,367,548                      |                                      |                     |
| R6.150.7 Hi-Profile and R6.165.7 Hi-Profile | 17,23         | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,320,014 |  | 10,367,771                      | 10,377,284                           |                     |
| R6.150.7 VRT and R6.165.7 VRT               | 17            | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,320,014 |  | 10,367,563                      | 10,377,146                           |                     |
| R6.175                                      | 2,17,22       | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,324,084 | 10,317,771                             | 10,367,771                      |                                      |                     |
| R6.175 Hi-Profile                           | 17,20         | 540/65 R28      |                       |     |        |     |     | X   | X   |     | 14,324,084 |  | 10,367,771                      | 10,377,307                           |                     |
| R6.180.7 Hi-Profile                         | 17,23         | 540/65 R34      |                       |     |        |     |     |     | X   |     | 14,322,874 |  | 10,367,771                      | 10,377,284                           |                     |
| R6.185                                      | 2,22          | 540/65 R34      |                       |     |        |     |     |     | X   |     | 14,324,064 | 10,317,771                             | 10,367,771                      |                                      |                     |
| R6.185 Hi-Profile                           | 20            | 540/65 R34      |                       |     |        |     |     |     | X   |     | 14,324,064 |  | 10,367,771                      | 10,377,307                           |                     |
|   |               |                 |                       |     |        |     |     |     |     |     |            |  |                                 |                                      |                     |
|   |               |                 |                       |     |        |     |     |     |     |     |            |  |                                 |                                      |                     |

2 Subframe adapted for tractors with or without front axle suspension.  
 15 With extended bearing boxes, the loader can be raised to max height, with the front windscreen fully open.  
 17 If the tractor have/should be equipped with Sauter front-hitch, contact Sauter for more information.  
 20 Hose kit Deluxe 10377307 does not fit tractors with air pressure equipment.  
 21 If the tractor is manufactured after 2006-09-01 order 10317771/10367771  
 22 Tractors manufactured after 2006-09-01 and without front axle suspension or piston pump a special plug is needed for L-S signal, order from SDF. Ref no:04454514.4  
 23 When fitting hose kit "Deluxe", 4 of the tractors quick couplers are moved to a higher position.  
 27 Tractor manufactured before 2006-09-01, tractor valve must be equipped with an end cover plate for LS signal, order from SDF. Ref no: Bosch 1525 503 538, SDFA 0441 3341