



ISSUE 01 APRIL 2010

<h1>Massey Ferguson</h1>			With Parallel Linkage								Alternative hydraulic solutions			
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85x DL	Subframe	ErgoDrive Standard Hydraulic Kit	ElectroDrive CDC Hydraulic Kit
Tractor model	Rem.	Max front wheel												
410 Cab, 410 ROPS, 420 Cab, 420 ROPS, 430 Cab and 430 ROPS		280/70 R20		X							14,321,455	10,317,738		
425, 435 and 440		12,4 R24			X						14,321,685	10,317,661		
431				X							14,321,454	10,317,535		
451		12,5/80 R18		X							14,321,674	10,317,736		
461		300/70R20		X							14,321,454	10,317,535		
471 Cab and 481 Cab		12,4 R24			X						14,321,814	10,317,737		
471 ROPS and 481 ROPS		12,4 R24			X						14,321,684	10,317,736		
491 Cab and 492 Cab	9	14,9 R24				X					14,321,975	10,317,737		
491 ROPS and 492 ROPS	9	14,9 R24				X					14,321,425	10,317,736		
533, 543 and 563		280/70 R20		X							14,321,454	10,317,806		
573 and 583	24	12,4 R24			X						14,323,595	10,317,737		
593 and 596	24,25	14,9 R24				X					14,321,425	10,317,737		
2430, 2435 and 2440	17,18	320/85R20		X	X						14,321,525	10,317,682	10,367,682	
3050, 3060 and 3065		14,9 R24			X	X					14,323,815	10,317,070		
3050 Steepnose, 3060 Steepnose and 3065 Steepnose		14,9 R24			X	X					14,323,825	10,317,070		
3435 model F and S, 3445 model F and S and 3455 model F and S	20,21	260/80 R20		X							14,322,074	10,317,525		
3615 Utility, 3625 Utility, 3635 Utility and 3645 Utility	23	12,4 R24		X							14,324,705	10,317,782		10,377,224
3625 model F, 3635 model F, 3645 model F and 3655 model F	44,45	320/70 R20		X							14,324,715	10,317,813		10,377,283
4225, 4235, 4245, 4255, 4325, 4335, 4345, 4355 and 4365	11	420/70 R24				X	X				14,320,915	10,317,537		

9 Use counter weight 1000 kg in combination with loader Q45.  
 11 Use counter weight 1200 kg in combination with loader Q55.  
 17 The subframe set will not fit tractors in Japan.  
 18 The subframe set will fit both model STD and GE.  
 20 Adapted for Cab, ROPS and Cab with ROPS  
 21 Will not fit tractor with hydraulic connections in front of Cab or outside the ROPS brackets.

23 Order hose set 10377224 if the tractor has a mid mounted valve.  
 24 Hydraulic set 10317808 adapted for tractors with ROPS.  
 25 Subframe set 14321425 adapted for tractors with ROPS.  
 44 Order hoseset 10377283 if the tractor has mid mounted valve.  
 45 Subframe set adapted for tractors with serial no as from T 35019.



ISSUE 01 APRIL 2010

<h1>Massey Ferguson</h1>			With Parallel Linkage								Alternative hydraulic solutions				
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85x DL	Subframe	ErgoDrive Standard Hydraulic Kit	ElectroDrive CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel													
4260, 4270, 4360 and 4370		13,6 R28					X	X			14,320,925	10,317,537			
4435, 4445 and 4455	8,14	480/65 R24			X	X					14,321,535	10,317,693	10,367,693		
5340, 5355 and 5360	19	14,9 R24			X	X					14,322,015	10,317,630			
5425 Dyna-4 Steepnose Tier2 & Tier3 and 5435 Dyna-4 Steepnose Tier2 & Tier3	7,10,22,30,31	14,9 R28			X	X	X				14,324,435	10,410,001	10,367,646		
5425 Dyna-4 Tier2 & Tier3 and 5435 Dyna-4 Tier2 & Tier3	7,10,22,30,31	14,9 R28			X	X	X				14,324,425	10,410,001	10,367,646		
5425 Speedshift and 5435 Speedshift	3,7,10,22,30,31	14,9 R28			X	X	X				14,322,625	10,410,001	10,367,646		
5425 Speedshift Steepnose and 5435 Speedshift Steepnose	3,7,10,22,30,31	14,9 R28			X	X	X				14,322,635	10,410,001	10,367,646		
5445 Dyna-4 Steepnose Tier2 & Tier3 and 5455 Dyna-4 Steepnose Tier2 & Tier3	7,10,30,31	14,9 R28				X	X				14,324,435	10,410,001	10,367,646		
5445 Dyna-4 Tier2 & Tier3 and 5455 Dyna-4 Tier2 & Tier3	7,10,30,31	14,9 R28				X	X				14,324,425	10,410,001	10,367,646		
5445 Speedshift and 5455 Speedshift	3,7,10,30,31	14,9 R28				X	X				14,322,625	10,410,001	10,367,646		
5445 Speedshift Steepnose and 5455 Speedshift Steepnose	3,7,10,30,31	14,9 R28				X	X				14,322,635	10,410,001	10,367,646		
5460 Dyna-4 Tier2 & Tier3	7,10,30,31	14,9 R28				X	X				14,324,425	10,410,001	10,367,646		
5460 Speedshift	3,7,10,30,31	14,9 R28				X	X				14,322,625	10,410,001	10,367,646		
5465 Dyna-4 Tier2	3,7,30,31	480/65 R28					X	X			14,321,305	10,410,001	10,367,646		
5465 Dyna-4 Tier3	6,13,30,31	16,9 R28					X	X	X		14,322,155	10,410,001	10,367,646		
5465 Dyna-4 Tier3 SISU Engine	6,30,31	16,9 R28					X	X	X		14,323,145	10,410,001	10,367,646		
5465 Speedshift	7,30,31	480/65 R28					X	X			14,320,455	10,410,001	10,367,646		
5470 Dyna-4 Tier2 & Tier3 and 5480 Dyna-4 Tier3	7,12,30,31,38	380/85 R28					X	X			14,324,885	10,410,001	10,367,646		

- 3 Subframe adapted for tractors with/without original 2.5 ton front hitch.
- 6 Subframe set will fit with and without original front hitch
- 7 Remove the lifting arms on the front hitch when using the loader
- 8 Subframe will fit all options except for Zuidberg front hitch.
- 10 Use counter weight 1000 kg in combination with loader Q55.
- 12 Use counter weight 1000 kg in combination with loader Q65.
- 13 Use counter weight 1000 kg in combination with loader Q75.
- 14 Loader Q35 must be ordered with long bearing boxes.

- 19 Hydraulic set 10317631 adapted for tractors with ROPS.
- 22 Loaders Q35 adapted for tractors with max. front wheel size 13,6 R24.
- 30 Ergodrive set 10410002 is adapted for Load sensing hydraulic system.
- 31 Electrodrive set 10367646 adapted for open centre.
- 38 Order mounting kit 5033878 for tractors with additional water separator with filter.



ISSUE 01 APRIL 2010

<h1>Massey Ferguson</h1>			With Parallel Linkage								Alternative hydraulic solutions				
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85x DL	Subframe	ErgoDrive Standard Hydraulic Kit	ElectroDrive CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel													
5475 Dyna-4 Tier3	6,13,30,31	16.9 R28						X	X		14,322,155	10,410,001	10,367,646		
5475 Dyna-4 Tier3 SISU engine	6,30	16.9 R28						X	X		14,323,145	10,410,001	10,367,646		
6110, 6120, 6130 and 6140		14.9 R24			X	X					14,323,815	10,317,224			
6110 Steepnose, 6120 Steepnose, 6130 Steepnose and 6140 Steepnose		14.9 R24			X	X					14,323,825	10,317,224			
6160, 6170 and 6180		14.9 R28					X	X			14,323,835	10,317,224			
6235, 6245 and 6255	15,16	480/65R28				X	X				14,321,925	10,317,324			
6260, 6270 and 6280	1	540/65 R28					X	X			14,320,295	10,317,625			
6265	15	480/65R28				X	X				14,321,925	10,317,324			
6290	1	540/65 R28						X			14,320,295	10,317,625			
6445 Dyna-6 Steepnose Tier2 & Tier3 and 6455 Dyna-6 Steepnose Tier2 & Tier3	5,7,10,26,33,37,42	14.9 R28				X	X				14,324,435	10,410,004	10,367,633	10,377,295	
6445 Dyna-6 Tier2 & Tier 3 and 6455 Dyna-6 Tier2 & Tier3	5,7,10,26,33,37,42	14.9 R28				X	X				14,324,425	10,410,004	10,367,633	10,377,295	
6445 Dynashift and 6455 Dynashift	3,5,7,10	14.9 R28				X	X				14,322,625	10,317,633	10,367,633	10,377,270	
6445 Dynashift Steepnose and 6455 Dynashift Steepnose	3,5,7,10	14.9 R28				X	X				14,322,635	10,317,633	10,367,633	10,377,270	
6460 Dyna-6 Tier2	5,7	14.9 R28				X	X				14,324,425	10,317,633	10,367,633		
6460 Dyna-6 Tier3 and 6470 Dyna-6 Tier3	5,7,12,26,32,33,38,43	380/85 R28					X	X			14,324,885	10,410,004	10,367,633	10,377,289	
6460 Dynashift and 6470 Dynashift	3,5,7	14.9 R28				X	X				14,322,625	10,317,633	10,367,633	10,377,270	

1 For open centre tractors, use hydraulic set 10317624.  
 3 Subframe adapted for tractors with/without original 2.5 ton front hitch.  
 5 Hydraulic kit 10317632/10367632 adapted for tractors with open centre hydraulics.  
 6 Subframe set will fit with and without original front hitch  
 7 Remove the lifting arms on the front hitch when using the loader  
 10 Use counter weight 1000 kg in combination with loader Q55.  
 12 Use counter weight 1000 kg in combination with loader Q65.  
 13 Use counter weight 1000 kg in combination with loader Q75.  
 15 Hydraulic kit 10317325 adapted for tractors with load sensing hydraulic system.  
 16 Subframe set 14321935 adapted for steepnose tractors.  
 26 Hose set Deluxe will only fit tractors with joystick in the armrest.  
 30 Ergodrive set 10410002 is adapted for Load sensing hydraulic system.

31 Electrodrive set 10367646 adapted for open centre.  
 32 Order Ergodrive 10317632 open centre or 10317770 load sensing for tractors with serial no up to T008085.  
 33 Ergodrive 10410003 adapted for tractors with open centre hydraulic system.  
 37 Order Ergodrive 10317632 open centre or 10317633 load sensing for tractors with serial no up to T008085.  
 38 Order mounting kit 5033878 for tractors with additional water separator with filter.  
 42 Order CDC-SMS Electro valve kit 10367834 load sensing for tractors with serial no as from T262090.  
 43 Order CDC-SMS Electro valve kit 10367835 load sensing for tractors with serial no as from T262090.



ISSUE 01 APRIL 2010

<h1>Massey Ferguson</h1>			With Parallel Linkage								Alternative hydraulic solutions				
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85x DL	Subframe	ErgoDrive Standard Hydraulic Kit	ElectroDrive CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel													
6465 Dyna-6	3,4,5,7,13,26	480/65 R28					X	X	X		14,321,305	10,317,770	10,367,633	10,377,287	
6465 Dyna-6 Tier3 SISU Engine, 6475 Dyna-6 Tier3 SISU Engine and 6480 Dyna-6 Tier3 SISU Engine	6,26,33	16.9 R28						X	X		14,323,145	10,410,004	10,367,835	10,377,287	
6465 Dynashift	3,4,5,7,13,26	480/65 R28					X	X	X		14,320,395	10,317,770	10,367,633	10,377,287	
6465 Tier3 Dyna-6	5,6,13,26,32,33,43	16.9 R28					X	X	X		14,322,155	10,410,004	10,367,633	10,377,287	
6470 Dyna-6 Tier2	5,7	14.9 R28				X	X				14,324,425	10,317,632	10,367,633		
6475 Dyna-6 and 6480 Dyna-6	3,4,5,7,13,26	480/65 R28						X	X		14,321,305	10,317,770	10,367,633	10,377,287	
6475 Dynashift and 6480 Dynashift	3,4,5,7,13,26	480/65 R28						X	X		14,320,395	10,317,770	10,367,633	10,377,270	
6475 Tier3 Dyna-6	5,6,13,26,32,33,43	16.9 R28						X	X		14,322,155	10,410,004	10,367,633	10,377,287	
6480 Tier3 Dyna-6	5,6,13,26,32,33,35,43	16.9 R28						X	X		14,324,205	10,410,004	10,367,633	10,377,287	
6485 Dynashift, 6490 Dynashift and 6495 Dynashift	26,36	480/70 R30							X		14,320,415	10,317,770	10,367,633	10,377,287	
6485 Tier3 Dyna-6, 6490 Tier3 Dyna-6 and 6495 Tier3 Dyna-6	6,26,34,43	16.9 R30							X		14,323,295	10,410,004	10,367,633	10,377,287	
6497 Dyna-6	6,7,26,34,39	600/65 R28							X		14,322,465	10,410,004	10,367,633	10,377,287	
6497 Dynashift and 6499 Dynashift	6,7,26	600/65 R28							X		14,320,865	10,317,673	10,367,673	10,377,178	
6497 Tier3 Dyna-6	6,26	600/65 R28								X	14,330,965	10,410,004	10,367,633	10,377,287	
6497 Tier3 Dyna-6	6,26	600/65 R28							X		14,323,295	10,410,004	10,367,633	10,377,287	
6499 Dyna-6	6,7,26,34,41	600/65 R28							X		14,322,465	10,410,004	10,367,633	10,377,287	
6499 Tier3 Dyna-6	6,26,40,43	600/65 R28								X	14,330,965	10,410,004	10,367,633	10,377,287	

3 Subframe adapted for tractors with/without original 2.5 ton front hitch.  
 4 Order subframe set 14320404 for tractors with 3,5ton front linkage.  
 5 Hydraulic kit 10317632/10367632 adapted for tractors with open centre hydraulics.  
 6 Subframe set will fit with and without original front hitch  
 7 Remove the lifting arms on the front hitch when using the loader  
 13 Use counter weight 1000 kg in combination with loader Q75.  
 26 Hose set Deluxe will only fit tractors with joystick in the armrest.  
 32 Order Ergodrive 10317632 open centre or 10317770 load sensing for tractors with serial no up to T008085.

33 Ergodrive 10410003 adapted for tractors with open centre hydraulic system.  
 34 Order Ergodrive 10317770 load sensing for tractors with serial no up to T008085.  
 35 Order subframe set 14322155 if for tractors with serial no before S337060.  
 36 Order subframe set 14320424 for tractors with 3.5 ton front linkage.  
 39 Subframe set fits tractors up to S/No T176049.  
 40 Subframe set designed for tractor with S/No from T198034.  
 41 Subframe set fits tractors up to S/No T197077.  
 43 Order CDC-SMS Electro valve kit 10367835 load sensing for tractors with serial no as from T262090.



ISSUE 01 APRIL 2010

<h1>Massey Ferguson</h1>			With Parallel Linkage								Alternative hydraulic solutions				
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85x DL	Subframe	ErgoDrive Standard Hydraulic Kit	ElectroDrive CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel													
6499 Tier3 Dyna-6	6,26,43	600/65 R28							X		14,323,295	10,410,004	10,367,633	10,377,287	
7465, 7475 and 7480	3,4,7,13,26	480/65 R28							X	X	14,320,435	10,317,770	10,367,633	10,377,269	
7465 Tier3, 7475 Tier3 and 7480 Tier3	6,13,26,34,43	16.9 R28							X	X	14,323,125	10,410,004	10,367,633	10,377,269	
7465 Tier3 SISU Engine, 7475 Tier3 SISU Engine and 7480 Tier3 SISU Engine	6,26	16.9 R28							X	X	14,323,135	10,410,004	10,367,835	10,377,269	
7485, 7490 and 7495	26,36	480/70 R30								X	14,320,445	10,317,770	10,367,633	10,377,269	
7485 Tier3, 7490 Tier3 and 7495 Tier3	6,26,34,43	16.9 R30								X	14,323,305	10,410,004	10,367,633	10,377,269	
7497 Dyna VT and 7499 Dyna VT	6,26	600/65 R28								X	14,331,015	10,410,004	10,367,835	10,377,287	
7497 Dyna VT and 7499 Dyna VT	6,26	600/65 R28								X	14,323,305	10,410,004	10,367,835	10,377,287	
8210 and 8220	2	470/70 R28								X	14,320,345	10,317,626			
8450, 8460, 8470 and 8480	26	16.9R30								X	14,330,115	10,317,703		10,377,218	
8650, 8660, 8670, 8680 and 8690	6,46	16.9R34								X	14,331,054		10,367,832		

2 Subframe adapted for tractors with Carraro front axle, with or without suspension.  
 3 Subframe adapted for tractors with/without original 2.5 ton front hitch.  
 4 Order subframe set 14320404 for tractors with 3,5ton front linkage.  
 6 Subframe set will fit with and without original front hitch  
 7 Remove the lifting arms on the front hitch when using the loader  
 13 Use counter weight 1000 kg in combination with loader Q75.  
 26 Hose set Deluxe will only fit tractors with joystick in the armrest.  
 34 Order Ergodrive 10317770 load sensing for tractors with serial no up to T008085.  
 36 Order subframe set 14320424 for tractors with 3.5 ton front linkage.  
 43 Order CDC-SMS Electro valve kit 10367835 load sensing for tractors with serial no as from T262090.  
 46 Front weight carrier must be removed.