



ISSUE 27 JANUARY 2010

<h1 style="text-align: center;">Claas</h1>			With Parallel Linkage								Without Parallel Linkage						Alternative hydraulic solutions					
			Q25 DS	Q25	Q35 DS	Q35	Q45	Q55	Q65	Q75	Q85x DL	Q20 DS	Q20	Q30 DS	Q30	Q40	Q50	Q60	Subframe	ErgoDrive Standard Hydraulic Kit	ElectroDrive CDC Hydraulic Kit	De Luxe Hose Kit
Tractor model	Rem.	Max front wheel																				
Ares 547, 557, 567 and 577	1,3,9,13,14	440/65 R28					X	X							X	X	14,323,565	10,317,723	10,367,562	10,377,276		
Ares 616, 626, 636, 656 and 696	1,3,7,8,9	480/65 R28						X	X							X	X	14,321,335	10,317,723	10,367,562		
Ares 617 and 657	1,3,9,12,14	480/65 R28						X	X							X	X	14,323,375	10,317,723	10,367,562	10,377,276	
Ares 697	1,3,9,14	480/65 R28						X	X							X	X	14,323,374	10,317,723	10,367,562	10,377,276	
Ares 816, 826 and 836	11,15	16,9 x 30								X							14,321,945	10,317,558	10,367,558			
Arion 410, 420 and 430	1	480/65 R28					X	X							X	X	14,325,115	10,317,866	10,367,866		10,377,309	
Arion 510, 520, 530 and 540 CIS/CEBIS	17,18,19,21	480/65 R28					X	X							X	X	14,323,715	10,317,815	10,367,815		10,377,293	
Arion 610 C and 620 C	17							X	X						X	X	14,324,405	10,317,816	10,367,816			
Arion 610 and 620 CIS/CEBIS	17,19,21	540/65 R28						X	X							X	X	14,324,405	10,317,815	10,367,815		10,377,293
Arion 630 C	16,17							X	X						X	X	14,324,405	10,317,816	10,367,816			
Arion 630 and 640 CIS/CEBIS	16,17,19,21	540/65 R28						X	X						X	X	14,324,405	10,317,815	10,367,815		10,377,293	
Axion 810, 820, 830 and 840 CIS/CEBIS/C-MATIC	17,20	600/70 R28								X							14,323,185		10,367,815	10,377,282		
Axion 850 CIS/CEBIS	17,20	600/70 R28								X							14,324,215		10,367,815	10,377,282		
Axos 310, 320, 330 and 340		340/85 R24					X	X							X	X	14,324,545	10,317,845	10,367,845			
Celtis 426, 436, 446 and 456	2,3,4,5,6	440/65R28					X	X							X	X	14,320,235	10,317,701	10,367,701			
Celtis 426 Rops, 436 Rops, 446 Rops and 456 Rops	2,4	440/65R28					X	X							X	X	14,320,235	10,317,664				

- 1 Subframe kit prepared with spacers for front linkage.
- 2 Use counter weight 1000 kg in combination with loader Q55 or Q50.
- 3 The joystick bracket in the CDC-kit can not be combined with "Renault Electro Pilot".
- 4 Subframe adapted for tractors with Lemoine Brillu front hitch. Will also fit tractors without front hitch.
- 5 ErgoDrive control valve is placed in another location than the subframe upright.
- 6 ElectroDrive control valve is placed in another location than the subframe upright.
- 7 Tractors with orig. 3.5T front linkage with horizontal connection with 4 bolts (prod. before 2005), kit 14321337 is required.
- 8 If tractor has original 3.5T front linkage, use 14321334.
- 9 If the tractor is equipped with open centre hydraulic system, use 10317724/10367653.
- 11 Subframe adapted for tractors with MX R38 front hitch. Will also fit models without front hitch.
- 12 If tractor has original 3.5T front linkage, use 14323374.
- 13 If tractor has original front linkage, use 14323564.

- 14 Utilisation of 3rd and 4th function together with Hose kit Std or De Luxe, requires CLAAS harness kit no. 7711132033 (ErgoPilot) or 7711132397 (ElectroPilot).
- 15 The CDC-kit does NOT include a joystick bracket.
- 16 If the tractor has an original reinforcement frame under the transmission, use 14324404.
- 17 The CDC-kit includes a joystick bracket, designed for tractors with multifunction armrest.
- 18 Hydraulic kit 10317816/10367816 is adapted for tractors with Open Center hydraulic system.
- 19 Hose kit 10377293 is adapted for mounting on the rear valve, for tractors with load sensing hydraulic system.
- 20 CDC kit 10367798 and hose kit 10377282 adapted for tractors with Bosch hydraulic system.
- 21 Hose kit 10377288 is adapted for tractors with a midmount valve.

