

NUGGET ROTASLASHERS

The best specified slashers
in their price range!



Optional
Front and Rear
Conveyor Belting
Safety Guards



ALL STANDARD FEATURES

- ✓ Heavy, 4mm, high shoulder steel body - no blocking in heavy conditions. (NUG100 has 3mm steel body).
- ✓ Adjustable side skids for accurate cutting height control.
- ✓ Friction clutch protection to safe-guard the tractor transmission.
- ✓ Latest design, high clearance two piece blade carrier.
- ✓ Forged, step-down blades for fine, even mowing.
- ✓ Built to Howard quality standards.
- ✓ Clean top with reinforcement underneath the body.

The Howard Nugget range of Rotaslashers is designed and built to meet our customer requirements for a tough, long-life, general purpose slasher at the right price.

NUGGET ROTASLASHERS



Nugget Rotaslashers are priced to compete, and specified to beat, all competitive machines within their price range. Many of the features from the larger Howard Rotaslashers are incorporated to ensure long service life and top performance.

To maintain the performance of your Nugget Rotaslasher, insist on genuine Howard wearing parts. They are available in boxed sets, because safety must never be compromised and new fasteners and journals must always be fitted with new blades.



Step down clearance gives clean cut and reduces wear.



Nugget General Specifications

Power Rating:	Recommended Tractor power ratings are (540 rpm PTO required): Nugget 100: From 15Kw to 34kW (20hp to 45hp) Nugget 150L: From 22kW to 34kW (29hp to 45hp) Nugget 120: From 18kW to 34kW (25hp to 45hp) Nugget 150: From 24kW to 56kW (32hp to 75hp) Nugget 135: From 22kW to 34kW (29hp to 45hp) Nugget 180: From 32kW to 56kW (43hp to 75hp)
Tractor Mounting:	Nugget 100 & 120: Cat 1 three point linkage (Alternately Cat 0). Nugget 135, 150, 150L and 180: Cat 1 three point linkage. Refer to table below for Mounting Offset. Top Link Slot to allow Rotaslasher to follow ground contours.
Bodies:	Bodies are manufactured from 4mm steel plate, reinforced and fitted with adjustable skids.
Drive Shaft:	Tri-lobal drive shafts are fitted, completely covered by a 'free-to-stop' safety guard. On Nugget 100, 120, 135 and 150L the uni-cross size is 27x75mm. On Nugget 150 and 180 the uni-cross size is 30x92mm.
Clutch:	A twin plate, shock protection clutch is fitted to the slasher gearbox.
Gearbox:	The gearboxes are single speed, purpose built models with nodular cast iron gear cases. The case hardened, alloy steel taper roller gears are supported by ball bearings in the gearboxes fitted to the Nugget 100, 120, 135 and 150L and by bearings in the gearbox fitted to the Nugget 150 and 180 Rotaslashers.
Blade Beam:	Latest design, high clearance two piece blade carrier.
Blades:	Drop forged, heat treated, step-down blades swinging on extra hard, cold forged bushes.
Optional Equipment:	Single puncture proof height control wheel. Front and Rear conveyor belting safety guards. (Note: Safety guards are now mandatory for slashers used in W.A).

Model	Cutting Width	Mounting Offset	Cutting Height	Blade Tip Speed	Weight
Nugget 100	1.0m (3'3")	Center or 7.5cm to LHS of Tractor	0 – 7.5cm on skids	55m/sec (10,740 ft/min)	140kg
Nugget 120	1.2m (4')	Center or 18cm to LHS of Tractor	0 – 7.5cm on skids	65m/sec (12,890 ft/min)	171kg
Nugget 135	1.37m (4'6")	Center or 18cm to LHS of Tractor	0 – 7.5cm on skids 0 – 11cm on wheels	75m/sec (14,760 ft/min)	250kg
Nugget 150L	1.52m (5')	Center or 17cm to LHS of Tractor	0 – 7.5cm on skids 0 – 11cm on wheels	83m/sec (16,400 ft/min)	320kg
Nugget 150	1.52m (5')	Center or 17cm to LHS of Tractor	0 – 7.5cm on skids 0 – 11cm on wheels	83m/sec (16,400 ft/min)	350kg
Nugget 180	1.83m (6')	Center or 18cm to LHS of Tractor	0 – 7.5cm on skids 0 – 11cm on wheels	100m/sec (19,680 ft/min)	375kg



If improperly used or maintained, Nugget Rotaslashers, like all powered machines, can cause bodily harm to operators and onlookers. Before operating the machine read the instruction book carefully and carry out all operating and maintenance recommendations.

Howard reserves the right to amend product specifications without notice. This leaflet is for illustration purposes and does not constitute an offer for sale.